

5 - Gang Wall Plate, Two Duplex and Three Toggle Openings, Night Black Brass, 120V/15A

- 5-gang configuration with two duplex and three toggle openings
- Brass construction in Night Black finish
- Rated 120 V at 15 A maximum current
- IP20 environmental rating for dry interior locations
- UL listed
- 1-year warranty

OVERVIEW

The C-VTG-AB-5-D-D-T-T-T is a 5-gang wiring device wall plate finished in Night Black, configured with two duplex receptacle openings and three toggle switch openings (DDTTT). It is intended for residential and light commercial supply applications where a unified, multi-device wall plate with a consistent dark finish is required across several switch and receptacle positions.

Constructed from brass, the plate is rated for 120 V service at 15 A and carries an IP20 environmental rating, suitable for standard interior dry-location installations. It is UL listed and backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime 50,000 h

ELECTRICAL

Operating Voltage 120 V

Maximum Current 15 A

Device Type Wall plate with duplex and toggle openings

Gangs 5

MECHANICAL

Finish NIGHT BLACK/ALL Black

Material Brass

ENVIRONMENTAL

IP Rating IP20

Environmental Rating Non - Waterproof

ORDERING

Warranty 1 y

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

Residential multi-switch and receptacle wall installations

Light commercial supply rooms

Multi-gang combination switch/receptacle panels

Interior dry-location electrical rooms

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	db	high
current_draw	15 A	db	high
device_type	Wall plate with duplex and toggle openings	pdf	medium
gang_count	5	pdf	high
finish	NIGHT BLACK/ALL Black	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY