

5 - Gang Brass Wall Plate, Decorator/GFCI/Triple USB Openings, Night Black, 120V/15A, UL Listed

- 5-gang configuration with one decorator opening, one GFCI opening, three USB openings
- Brass construction with Night Black/All Black finish
- Rated 120V at 15A for standard residential and commercial circuits
- IP20 environmental rating, classified Non-Waterproof for dry locations
- UL listed
- 1-year warranty

OVERVIEW

The C-VTG-AB-5-D-G-U-U-U is a 5-gang wall plate assembly built from brass and finished in Night Black/All Black for a uniform dark aesthetic across multi-device installations. The configuration combines one decorator opening, one GFCI opening, and three USB openings, allowing switching, ground-fault protection, and device charging to be consolidated into a single plate.

The assembly is rated for 120V operation at 15A and carries an IP20 environmental rating, classified as Non-Waterproof, making it appropriate for dry interior locations rather than wet or exposed areas.

The device is UL listed and backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime 50,000 h

MECHANICAL

Finish NIGHT BLACK/ALL Black

Material Brass

ORDERING

Warranty 1 y

ELECTRICAL

Operating Voltage 120 V

Maximum Current 15 A

Device Type Wall plate assembly

Gangs 5

ENVIRONMENTAL

IP Rating IP20

Environmental Rating Non-Waterproof

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Interior residential wall installations
- Multi-device gang boxes in commercial buildouts
- Kitchen or office charging stations combining USB and switching
- Dry-location device panels requiring ground-fault protection

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	db	high
current_draw	15 A	db	high
device_type	Wall plate assembly	pdf	medium
gang_count	5	pdf	high
finish	NIGHT BLACK/ALL Black	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY