

5 - Gang Wall Plate, Night Black Finish, Two GFCI and Three Toggle Openings, 120V/15A

- Five-gang layout with two GFCI and three toggle openings
 - Night Black/All Black finish across all openings
 - Brass construction for device durability
- Rated 120V at 15A maximum current draw
 - IP20 rated for standard indoor dry-location use
 - UL listed with 1-year warranty

OVERVIEW

The C-VTG-AB-5-G-G-T-T-T is a 5-gang wall plate finished in Night Black/All Black, configured with two GFCI receptacle openings and three toggle switch openings. It suits residential and light commercial supply installations where a uniform all-black device layout is specified across a multi-gang run.

Constructed from brass and rated for 120V/15A service, the plate carries an IP20 rating for standard indoor dry-location use and a Non-Waterproof environmental rating.

The device is UL listed and carries a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime50,000 h

ELECTRICAL

Operating Voltage120 V

Maximum Current15 A

Device TypeWall plate with GFCI and toggle switch openings

Gangs5

MECHANICAL

FinishNIGHT BLACK/ALL Black

MaterialBrass

ENVIRONMENTAL

IP RatingIP20

Environmental RatingNon-Waterproof

ORDERING

Warranty1 y

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Residential multi-gang wall installations
- Light commercial supply rooms
- Hallway or utility room switch banks
- Indoor dry-location device panels

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high

slug	value	source	confidence
operating_voltage	120 V	db	high
current_draw	15 A	db	high
device_type	Wall plate with GFCI and toggle switch openings	pdf	high
gang_count	5	pdf	high
finish	NIGHT BLACK/ALL Black	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY