

3-Gang Wiring Device Plate with Toggle and Two USB Openings, 120V/15A, Black and Gold

- Configured with one toggle opening and two USB openings in a 3-gang layout
- Brass construction for the cover plate body
- Rated 120V at 15A for standard branch circuit devices
- IP20 rated, non-waterproof, for dry indoor use only
- UL listed
- Backed by a 1-year warranty

OVERVIEW

The C-VTG-BG-3-T-U-U is a 3-gang wiring device plate finished in black and gold, configured with one toggle opening and two USB openings for combined switch and charging port installations. It is intended for use in residential and light commercial wall box assemblies where multiple device types are consolidated into a single cover plate.

Constructed from brass, the plate is rated for 120V at 15A, suitable for standard branch circuit wiring devices. The IP20 environmental rating and non-waterproof classification indicate suitability for dry indoor locations only.

The plate is UL listed and carries a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime	50,000 h
--------------	----------

ELECTRICAL

Operating Voltage	120 V
-------------------	-------

Current Draw	15 A
--------------	------

MECHANICAL

Finish	BLACK AND GOLD
--------	----------------

Material	Brass
----------	-------

ENVIRONMENTAL

IP Rating	IP20
-----------	------

Environmental Rating	Non-Waterproof
----------------------	----------------

ORDERING

Warranty	1 y
----------	-----

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Residential wall switch and receptacle boxes
- Multi-gang device installations in living areas
- Home office or workstation charging stations
- Kitchen and bath device plate assemblies

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	db	high
current_draw	15 A	db	high
finish	BLACK ANG GOLD	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY