

5-Gang Wall Plate, Two Duplex, One GFCI, Two Toggle Openings, Bronze with Patina Brass

- Five-gang configuration with two duplex, one GFCI, and two toggle openings
- Brass construction with bronze with patina finish
- Rated for 120 V circuits at up to 15 A
- IP20 rated for non-waterproof, indoor dry-location installation
- UL listed assembly
- Backed by a 1-year warranty

OVERVIEW

The C-VTG-BP-5-D-D-G-T-T is a five-gang brass wall plate finished in bronze with patina, configured with two duplex receptacle openings, one GFCI receptacle opening, and two toggle switch openings. It is intended for residential supply applications requiring a combination of outlet and switch control within a single multi-gang assembly.

Constructed from brass, the plate is rated for 120 V circuits at up to 15 A and carries an IP20 rating for standard indoor dry-location use, with a non-waterproof environmental rating.

The assembly is UL listed and backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime	50,000 h
--------------	----------

ELECTRICAL

Operating Voltage	120 V
-------------------	-------

Current Draw	15 A
--------------	------

MECHANICAL

Finish	BRONZE WITH PATINA
--------	--------------------

Material	Brass
----------	-------

ENVIRONMENTAL

IP Rating	IP20
-----------	------

Environmental Rating	Non-Waterproof
----------------------	----------------

ORDERING

Warranty	1 y
----------	-----

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Residential kitchen and utility rooms
- Multi-device wall assemblies in living spaces
- Home renovation projects requiring combined outlet and switch control
- Indoor dry-location residential wiring

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	db	high
current_draw	15 A	db	high
finish	BRONZE WITH PATINA	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY