

3 - Gang Wall Plate, Decorator/GFCI/USB Configuration, Satin Brass, 120V 15A, UL Listed

- 3-gang configuration with decorator, GFCI, and USB openings
 - Solid brass construction with satin brass finish
 - Rated for 120V operation at 15A maximum current
- IP20 rated, classified as non-waterproof for interior use
 - UL listed device
 - Backed by a 1-year warranty

OVERVIEW

The C-VTG-SB-3-D-G-U is a satin brass 3-gang wall plate assembly built for residential and light commercial supply applications. The configuration includes one decorator opening, one GFCI opening, and one USB opening, allowing multiple device types to be mounted at a single wall location.

The assembly is rated for 120V operation and 15A current draw, with a brass construction and satin brass finish. It carries an IP20 rating and is classified as non-waterproof, making it suitable for standard interior installations.

The device is UL listed and backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime50,000 h

ELECTRICAL

Operating Voltage120 V

Maximum Current15 A

Device TypeWall Plate Assembly

Gangs3

MECHANICAL

FinishSATIN BRASS

MaterialBrass

ENVIRONMENTAL

IP RatingIP20

Environmental RatingNon-Waterproof

ORDERING

Warranty1 y

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Residential wall outlet and switch locations
- Light commercial interior wiring installations
- Kitchen and bath combination device mounting
- Multi-device wall stations requiring USB charging
- Retrofit upgrades for vintage-style interiors

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	db	high
current_draw	15 A	db	high
device_type	Wall Plate Assembly	pdf	high
gang_count	3	pdf	high
finish	SATIN BRASS	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY