

4 - Gang Wall Plate, Two Duplex Openings, GFCI and Switch, Satin Brass, 120V 15A

- 4-gang configuration with two duplex, one GFCI and one switch opening
- Brass construction with a satin finish
- Rated for 120V service at 15A maximum current
- IP20 rated for standard indoor dry-location use
- UL listed
- Backed by a 1-year warranty

OVERVIEW

The C-VTG-SB-4-D-D-G-S is a satin brass 4-gang wall plate configured for two duplex receptacle openings, one GFCI opening and one switch opening. It is intended for residential supply applications where multiple device types are grouped under a single coordinated finish.

Constructed from brass with a satin finish, the plate is rated for 120V service at 15A and carries an IP20 rating for standard indoor dry-location use.

The device is UL listed and backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime 50,000 h

ELECTRICAL

Operating Voltage	120 V
Maximum Current	15 A
Device Type	Wall Plate
Gangs	4

MECHANICAL

Finish	SATIN BRASS
Material	Brass

ENVIRONMENTAL

IP Rating	IP20
Environmental Rating	Non - Waterproof

ORDERING

Warranty 1 y

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Residential renovation projects
- Multi-device wall installations
- Custom electrical device panels
- Decorative trim upgrades for mixed device groupings

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	db	high
current_draw	15 A	db	high
device_type	Wall Plate	pdf	medium
gang_count	4	pdf	high
finish	SATIN BRASS	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY