

4 - Gang Wall Plate with Two Decorator, GFCI and Toggle Openings, Satin Brass, 120V 15A UL Listed

- Four-gang configuration with two decorator, one GFCI and one toggle opening
- Constructed from brass with a satin brass finish
- Rated for 120V service at 15A maximum current
- IP20 rated for standard indoor dry-location use
- Non-waterproof environmental rating
- UL listed and backed by a 1-year warranty

OVERVIEW

The C-VTG-SB-4-D-D-G-T is a satin brass 4-gang wall plate configured with two decorator openings, one GFCI opening, and one toggle opening. It is designed for residential supply applications where multiple device types are grouped in a single gang location, providing a coordinated finish across the assembly.

Constructed from brass with a satin finish, the plate is rated for 120V/15A service and carries an IP20 rating, suitable for standard indoor dry-location installations. It carries a non-waterproof environmental rating and is UL listed.

The assembly is backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime50,000 h

ELECTRICAL

Operating Voltage120 V
Maximum Current15 A
Gangs4

MECHANICAL

FinishSATIN BRASS
MaterialBrass

ENVIRONMENTAL

IP RatingIP20
Environmental RatingNon-Waterproof

ORDERING

Warranty1 y

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Residential multi-device wall gangs
- Kitchen and bathroom switch and receptacle groupings
- Renovation projects requiring coordinated device finishes
- Multi-function control locations in living areas

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high

slug	value	source	confidence
operating_voltage	120 V	db	high
current_draw	15 A	db	high
gang_count	4	pdf	high
finish	SATIN BRASS	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY