

4-Gang Wall Plate, Two Duplex and Two Single Openings, 15A 120V, Satin Brass

- Four-gang brass wall plate with satin brass finish
- Configured with two duplex openings and two single openings
- Rated for 120 V circuits at up to 15 A
- IP20 rating for indoor dry-location use
- UL listed for compliance verification
- Backed by a 1-year warranty

OVERVIEW

The C-VTG-SB-4-D-D-S-S is a satin brass 4-gang wall plate configured with two duplex openings and two single openings. It is intended for residential supply applications where a mix of outlet and switch device configurations must be accommodated within a single multi-gang assembly.

Constructed from brass with a satin finish, the plate is rated for 120 V circuits at up to 15 A and carries an IP20 rating, suitable for standard indoor dry-location installations.

The plate is UL listed and backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime 50,000 h

ELECTRICAL

Operating Voltage 120 V

Maximum Current 15 A

Device Type Wall Plate - Two Duplex and Two Single Openings

Gangs 4

MECHANICAL

Finish SATIN BRASS

Material Brass

ENVIRONMENTAL

IP Rating IP20

Environmental Rating Non-Waterproof

ORDERING

Warranty 1 y

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

Residential kitchen and living area outlet walls

Multi-device wiring stations combining outlets and switches

Renovation projects requiring vintage-style hardware

Home office or media room device clusters

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	db	high
current_draw	15 A	db	high
device_type	Wall Plate - Two Duplex and Two Single Openings	pdf	high
gang_count	4	pdf	high
finish	SATIN BRASS	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY