

4-Gang Wall Plate, Satin Brass, Three GFCI Openings and One Toggle, 120V/15A

- 4-gang configuration with three GFCI openings and one toggle opening
- Satin brass finish over brass construction
- Rated for 120 V service at 15 A
- IP20 rating for indoor dry-location use
- UL listed
- 1-year warranty

OVERVIEW

The C-VTG-SB-4-G-G-G-T is a satin brass 4-gang wall plate built to order with three GFCI receptacle openings and one toggle switch opening (GGGT configuration). It is intended for residential supply installations where multiple device types are combined behind a single coordinated plate, such as kitchens, bathrooms, and utility rooms.

Constructed from brass with a satin finish, the plate is rated for 120 V service at 15 A and carries an IP20 rating for standard indoor dry-location use.

The device is UL listed and carries a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime 50,000 h

ELECTRICAL

Operating Voltage 120 V

Maximum Current 15 A

Device Type Wall Plate with GFCI Receptacle and Toggle Switch Openings

Gangs 4

MECHANICAL

Finish SATIN BRASS

Material Brass

ENVIRONMENTAL

IP Rating IP20

Environmental Rating Non - Waterproof

ORDERING

Warranty 1 y

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

Kitchens Bathrooms Utility rooms Residential multi-device wall assemblies

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	db	high
current_draw	15 A	db	high
device_type	Wall Plate with GFCI Receptacle and Toggle Switch Openings	pdf	medium
gang_count	4	pdf	high
finish	SATIN BRASS	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY