

5 - Gang Wall Plate, Satin Brass, Three Duplex and Two GFCI Openings, 120V/15A

- Five-gang configuration with three duplex and two GFCI openings
- Satin brass finish over brass construction
- Rated for 120 V circuits at up to 15 A
- IP20 rating for indoor dry-location use
- UL listed for compliance verification
- Backed by a 1-year warranty

OVERVIEW

The C-VTG-SB-5-D-D-D-G-G is a satin brass 5-gang wall plate configured with three duplex receptacle openings and two GFCI receptacle openings. It is intended for residential and light commercial installations where multiple receptacle types must be combined under a single finished cover plate.

Constructed from brass with a satin finish, the plate is rated for 120 V circuits at up to 15 A and carries an IP20 rating for standard indoor dry locations.

The device is UL listed and backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime	50,000 h
--------------	----------

ELECTRICAL

Operating Voltage	120 V
-------------------	-------

Current Draw	15 A
--------------	------

MECHANICAL

Finish	SATIN BRASS
--------	-------------

Material	Brass
----------	-------

ENVIRONMENTAL

IP Rating	IP20
-----------	------

Environmental Rating	Non - Waterproof
----------------------	------------------

ORDERING

Warranty	1 y
----------	-----

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

Residential kitchen and bathroom receptacle banks

Light commercial office receptacle walls

Multi-unit residential common areas

Finished basement or utility room installations

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	db	high
current_draw	15 A	db	high
finish	SATIN BRASS	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY