

## Satin Brass 5-Gang Wall Plate, Two Duplex, Two GFCI, One Toggle, 120V/15A

- Five-gang configuration with two duplex, two GFCI and one toggle opening
- Brass construction with a satin brass finish
- Rated for 120 V circuits at 15 A
- IP20 environmental rating for indoor dry locations
- UL listed
- 1-year warranty

### OVERVIEW

The C-VTG-SB-5-D-D-G-G-T is a satin brass 5-gang wall plate configured with two duplex openings, two GFCI openings, and one toggle opening. It is intended for residential and light commercial installations where multiple device types must be accommodated within a single gang arrangement, providing a unified, finished appearance.

Constructed from brass with a satin finish, the plate is rated for 120 V circuits at 15 A and carries an IP20 environmental rating, suitable for standard indoor dry locations.

The plate is UL listed and carries a 1-year warranty.

### SPECIFICATIONS

#### OPTICAL

|              |          |
|--------------|----------|
| LED Lifetime | 50,000 h |
|--------------|----------|

#### ELECTRICAL

|                   |       |
|-------------------|-------|
| Operating Voltage | 120 V |
|-------------------|-------|

|              |      |
|--------------|------|
| Current Draw | 15 A |
|--------------|------|

#### MECHANICAL

|        |             |
|--------|-------------|
| Finish | SATIN BRASS |
|--------|-------------|

|          |       |
|----------|-------|
| Material | Brass |
|----------|-------|

#### ENVIRONMENTAL

|           |      |
|-----------|------|
| IP Rating | IP20 |
|-----------|------|

|                      |                  |
|----------------------|------------------|
| Environmental Rating | Non - Waterproof |
|----------------------|------------------|

#### ORDERING

|          |     |
|----------|-----|
| Warranty | 1 y |
|----------|-----|

### CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Residential multi-device wall installations
- Light commercial device gang plates
- Kitchen and bathroom combination outlet layouts
- Renovation projects requiring mixed device types

PROVENANCE — REVIEW COPY ONLY

| slug                 | value            | source | confidence |
|----------------------|------------------|--------|------------|
| led_lifetime_h       | 50,000 h         | db     | high       |
| operating_voltage    | 120 V            | db     | high       |
| current_draw         | 15 A             | db     | high       |
| finish               | SATIN BRASS      | db     | high       |
| material             | Brass            | db     | high       |
| ip_rating            | IP20             | db     | high       |
| environmental_rating | Non - Waterproof | db     | high       |
| warranty_years       | 1 y              | db     | high       |

Specifications subject to change without notice.

REVIEW COPY