

Satin Brass 5-Gang Wall Plate, One Decorator and Three Toggle Openings and One USB, 120V/15A, UL Listed

- Satin brass finish over solid brass construction
- 5-gang configuration with decorator, toggle and USB openings
- Rated for 120V, 15A electrical service
- IP20 rated for non-waterproof interior use
- UL listed for code-compliant installations
- Backed by a 1-year warranty

OVERVIEW

The C-VTG-SB-5-D-T-T-T-U is a satin brass 5-gang wall plate configured with one decorator opening, three toggle openings and one USB opening. It is built for commercial and residential wiring applications where multiple device types are combined in a single gang arrangement, reducing the need for separate plates in mixed-device installations.

The plate is rated for 120V, 15A service and constructed of brass with a satin brass finish. It carries an IP20 rating and is classified non-waterproof, suited for standard interior wall installations.

The device is UL listed and backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime	50,000 h
--------------	----------

ELECTRICAL

Operating Voltage	120 V
-------------------	-------

Current Draw	15 A
--------------	------

MECHANICAL

Finish	SATIN BRASS
--------	-------------

Material	Brass
----------	-------

ENVIRONMENTAL

IP Rating	IP20
-----------	------

Environmental Rating	Non-Waterproof
----------------------	----------------

ORDERING

Warranty	1 y
----------	-----

CERTIFICATIONS & COMPLIANCE



UL Listed

APPLICATIONS

- Residential multi-switch wall installations
- Commercial office wiring device panels
- Mixed-device gang boxes combining switches and USB
- Renovation projects requiring consolidated wall plates

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	db	high
current_draw	15 A	db	high
finish	SATIN BRASS	db	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY