



Double Outlet GFCI Receptacle, 120V
15A, Brass, All-Black Finish, UL Listed

- Double outlet GFCI configuration for two-device protection
- Rated for 120 VAC service at a 15A maximum load
- Brass construction for device contacts and components
- IP20 ingress protection rating for indoor use
- Non-Waterproof environmental rating
- UL Listed, file number E481372-20200313

OVERVIEW

The C-VTG-SO2-GFCI-AB is a double outlet GFCI receptacle finished in all-black (Night Black) for applications requiring a uniform dark aesthetic. It is rated for 120 VAC service at a 15A load and provides ground fault circuit interrupter protection for general-purpose branch circuits.

Constructed with brass components, the receptacle carries a Non-Waterproof environmental rating and an IP20 ingress protection rating, suitable for standard indoor installations.

The device is UL Listed (file number E481372-20200313) and is backed by a 1-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime 50,000 h

MECHANICAL

Finish All-Black (Night Black)

Material Brass

COMPLIANCE

UL File Number E481372-20200313

ELECTRICAL

Operating Voltage 120 V

Maximum Current 15 A

Device Type GFCI Receptacle

Gangs 2

ENVIRONMENTAL

IP Rating IP20

Environmental Rating Non-Waterproof

ORDERING

Warranty 1 y

CERTIFICATIONS & COMPLIANCE



UL Listed
E481372-20200313

APPLICATIONS

- Residential kitchens and bathrooms
- Indoor general-purpose branch circuits
- Commercial break rooms
- Multi-family residential units

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120 V	db	high
current_draw	15 A	db	high
device_type	GFCI Receptacle	pdf	high
gang_count	2	pdf	medium
finish	All - Black (Night Black)	pdf	high
material	Brass	db	high
ip_rating	IP20	db	high
environmental_rating	Non - Waterproof	db	high
ul_file_number	E481372 - 20200313	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY