



Triple Wire Connector, 800V/8A Rated,
35x9.5x6mm, 0.3-0.75mm2 Wire
Range

- Rated for 800V at 8A per connector
- Accepts wire cross-sections from 0.3 to 0.75mm2
- Compact housing measures 35 × 9.5 × 6mm
- Supplied in packs of 5 pairs
- Joins three conductors in a single connector body

OVERVIEW

This triple wire connector provides a compact mechanical splice point for joining three conductors within a single housing. It is suited for electrical panels, junction boxes and low-voltage wiring runs where a quick, tool-free connection is required.

The connector is rated for 800V and 8A, accommodating wire gauges from 0.3 to 0.75mm2. Overall housing dimensions measure 35 × 9.5 × 6mm, allowing installation in space-constrained enclosures. Units are supplied in packs of 5 pairs.

SPECIFICATIONS

ELECTRICAL

Operating Voltage	800 V
Current Draw	8 A
Wire Gauge *	0.75 AWG

MECHANICAL

Product Dimensions	35×9.5×6mm
--------------------	------------

APPLICATIONS

- Electrical junction boxes
- Low-voltage panel wiring
- LED strip and fixture wire splicing
- Control cabinet terminations

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
operating_voltage	800 V	pdf	high
current_draw	8 A	pdf	high
wire_gauge	0.75 AWG	pdf	low
product_dimensions	35×9.5×6mm	pdf	high

* Value inferred from source data; verify before specification.
Specifications subject to change without notice.