

Duplex Receptacle with Dual USB Charging Ports, 15A 125V, Tamper-Resistant

OVERVIEW

The E-O-15A-USB is a tamper-resistant duplex receptacle with integrated dual USB charging ports, designed for commercial installations where device charging is required without adapters or wall blocks. The unit includes one Type-A and one Type-C USB port, allowing simultaneous charging of two devices from a single outlet location.

The receptacle is rated 15A 125V 60Hz with a USB output of 5VDC at 4.2A. A built-in smart charging chip identifies each connected device's power requirements to optimize charge delivery. The polycarbonate enclosure carries a UL94-V0 flame classification. Wiring accepts 12–14 AWG conductors via side-wire or back-wire terminations. Tamper-resistant shutters are incorporated into both the AC slots and USB ports to reduce the risk of foreign object insertion.


The receptacle is cETLus listed to UL 498 and CSA C22.2 No. 42-10, confirming compliance with both U.S. and Canadian safety standards. No warranty term is specified in the available product documentation.

SPECIFICATIONS

Input voltage	125V V	Dimensions	15.35 x 10.63 x 9.84 in
Weight	7.1 kg		

MOUNTING

Certification	cETLus	Standard(s)	UL 498&CSA C22.2 No. 42-10
Technical parameter	Receptacle Rating:15A 125V 60Hz		Packing Details:
	USB Rating:5VDC, 4.2A		50pcs/CTN
	Dielectric Voltage Withstand:1.25KV/1min		N.W.:7.1KG
	Flame Classifications:UL94-V0		G.W.:8KG
	Wire:12-14AWG		Size:15.35*10.63*9.84 inch



CERTIFICATIONS & COMPLIANCE



ETL Listed