



Edge Lit Exit Light, Double Face, 1.2 W, 120-347 VAC, 120-Minute Battery, UL 924 Listed

- Aluminum housing with UL-94-V0 flame-retardant acrylic diffuser
- 1.2 W input rating across 120-347 VAC 60 Hz supply
- Maintenance-free 3.6 V NiCad battery, 120-minute discharge
- 24-hour recharge cycle with fully illuminated 6-inch characters
- UL 924 Listed for damp locations, CEC Title 20 compliant
- Wall, ceiling and end mounting in a 310 × 257 × 110 mm silver enclosure

OVERVIEW

Double-face edge lit exit light with an aluminum housing and high grade acrylic diffuser, illuminating 6-inch legend characters in red or green. Wall, ceiling and end mounting positions suit corridors, stairwells, assembly areas and other egress paths requiring continuously identified exits.

Long-life, high-intensity LEDs draw 1.2 W across a 120-347 VAC 60 Hz input, with a maintenance-free 3.6 V NiCad battery that reaches full charge in 24 hours and supports 120 minutes of emergency discharge. Rated for 0°C to 40°C ambient operation in a silver finish, 310 × 257 × 110 mm housing built from UL-94-V0 flame-retardant material.

UL 924 Listed for damp locations and CEC Title 20 compliant, and meets NFPA 101 Life Safety Code, NEC and OSHA requirements. Covered by a 3-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime 50,000 h

MECHANICAL

Product Dimensions 310*257*110mm

Finish Silver

Material Aluminum

Mounting Wall/Pole Mount

COMPLIANCE

UL File Number 924

ELECTRICAL

Operating Voltage 120-347 V

Wattage 1.2 W

ENVIRONMENTAL

IP Rating IP20

Environmental Rating Non-Waterproof

Ambient Operating Temperature 0-40 °C
32-104 °F

ORDERING

Warranty 3 y

CERTIFICATIONS & COMPLIANCE



UL Listed
924

APPLICATIONS

- Egress corridors and stairwells
- Assembly and retail spaces
- Office and institutional buildings
- Parking structure walkways
- Warehouse exit paths

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120–347 V	pdf	high
wattage	1.2 W	pdf	high
product_dimensions	310*257*110mm	pdf	high
finish	Silver	db	high
material	Aluminum	db	high
mount_type	Wall/Pole Mount	db	high
ip_rating	IP20	db	high
environmental_rating	Non-Waterproof	db	high
ambient_temp_c	0–40 °C	pdf	high
ul_file_number	924	db	high
warranty_years	3 y	db	high

Specifications subject to change without notice.

REVIEW COPY