



Edge Lit Emergency Exit Light, Single Face, 1.2 W, 120-347 VAC, 120-Minute Discharge, UL 924

- Aluminum housing with UL-94-V0 flame-retardant acrylic diffuser
- 1.2 W input rating across a 120-347 VAC, 60 Hz range
- Maintenance-free 3.6 V NiCad battery, 200 mAh, 24-hour recharge
- 120-minute discharge time on loss of normal power
- Fully illuminated 6-inch single-face legend, silver finish
- UL 924 Listed for damp locations and CEC Title 20 compliant

OVERVIEW

Single-face edge lit exit light with an aluminum housing and high grade acrylic diffuser, using long-life high-intensity LEDs to illuminate 6-inch characters. Wall, ceiling and end mounting allow the unit to be placed at egress doors, corridors and stair landings in commercial and institutional buildings.

Input rating is 1.2 W at 120-347 VAC, 60 Hz, with a maintenance-free 3.6 V NiCad battery rated at 200 mAh. The battery recharges in 24 hours and supports 120 minutes of discharge. Housing material is UL-94-V0 flame-retardant, the finish is silver, and the unit operates from 0°C to 40°C. LED lifetime is rated at 50,000 hours.

UL 924 Listed for damp locations and CEC Title 20 compliant. Backed by a 3-year warranty.

SPECIFICATIONS

OPTICAL

LED Lifetime 50,000 h

MECHANICAL

Product Dimensions 310*257*110mm

Finish Silver

Material Aluminum

Mounting Wall/Pole Mount

COMPLIANCE

UL File Number 924

ELECTRICAL

Operating Voltage 120-347 V

Wattage 1.2 W

ENVIRONMENTAL

IP Rating IP20

Environmental Rating Non-Waterproof

Ambient Operating Temperature 0-40 °C
32-104 °F

ORDERING

Warranty 3 y

CERTIFICATIONS & COMPLIANCE



UL Listed
924

APPLICATIONS

- Egress doors and exit corridors
- Stairwells and stair landings
- Office and retail build-outs
- School and healthcare corridors
- Warehouse and light industrial egress paths

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
led_lifetime_h	50,000 h	db	high
operating_voltage	120–347 V	pdf	high
wattage	1.2 W	pdf	high
product_dimensions	310*257*110mm	pdf	high
finish	Silver	db	high
material	Aluminum	db	high
mount_type	Wall/Pole Mount	db	high
ip_rating	IP20	db	high
environmental_rating	Non-Waterproof	db	high
ambient_temp_c	0–40 °C	pdf	high
ul_file_number	924	db	high
warranty_years	3 y	db	high

Specifications subject to change without notice.

REVIEW COPY