

## Combo LED Exit Sign with Adjustable Emergency Heads, 120/277V, UL Listed

### OVERVIEW

The EM-EBS2x1-R-L is a combination LED exit sign and emergency lighting unit designed for commercial and industrial applications requiring both egress signage and backup illumination in a single fixture. The unit supports wall and ceiling mounting and accepts 120/277VAC, 60Hz dual-voltage input, making it suitable for a range of building electrical configurations.

The housing is constructed from injection-molded thermoplastic ABS rated UL-94V-0 for flame retardancy. The unit operates on super-bright SMD LEDs and includes a nickel cadmium battery for emergency backup, with a charge indicator light and test switch for routine inspection. Overcharge and over-discharge protection are built in. Emergency duration exceeds 90 minutes per the product datasheet.

No certification listings are confirmed in the available source data. Installers should verify applicable local code compliance and listing requirements prior to specification.

### SPECIFICATIONS

<b>Power</b>	4 W	<b>Dimensions</b>	11.02 x 4.56 x 2.67 in
<b>Input voltage</b>	120/277 VAC		

### DIMENSION



- IMPORTANT SAFETY GUIDES**
- When using electrical equipment basic safety precautions should always be followed including the following:
  - Read and follow all safety instructions.
- READ AND FOLLOW ALL SAFETY INSTRUCTIONS**
- When using electrical equipment basic safety precautions should always be followed, including the following:
  - Do not use power before performing work on electrical equipment.
  - Do not use outdoors.
  - Do not let power cords touch hot surfaces.
  - Do not touch the equipment for other than its intended purpose.
  - Do not use the equipment for other than its intended purpose.
  - Servicing of this equipment should be performed by qualified service personnel.
  - Equipment shall be installed in locations and heights where it will not be subject to tampering by unauthorized personnel.