

Recessed Edgelit Aluminum Exit Sign, 120/277V, Single or Double Face

OVERVIEW

The RELZXTE Recessed Edgelit Aluminum Exit Sign is designed for recessed ceiling installation in commercial and institutional applications. Available in single or double face configurations with red or green LED illumination, the unit features a UV-stabilized ultra-clear acrylic edgelit panel for consistent, uniform light distribution across the sign face.

The sign operates on dual 120/277V input (50/60Hz) and is rated for ambient temperatures from 0°C to 50°C. Battery backup (EM) models include a 4.8V NiCd rechargeable battery with a 24-hour recharge time and a minimum 90-minute emergency discharge duration. The extruded aluminum housing accepts optional black or white powder-coated trim finishes. Optional configurations include self-diagnostics (SDT), wall mount (WM), dual circuit, and 208/220/240V special voltage.

The unit is UL Listed for damp locations and meets UL924, NFPA 101, NEC, and OSHA requirements. It is also certified to CEC Title 20 Regulations. All electronics and housing carry a five-year warranty; the battery is prorated for five years.

SPECIFICATIONS

Input voltage	120/277V dual voltage standard; 208/220/240V optional	Warranty	5 years
Operating temp	0-50°C	Dimensions	15.75 x 11.5 x 4.375 (wall mount); panel: 11 x 10.5625 in

CERTIFICATIONS & COMPLIANCE



UL Listed