



20W LED Flood Light, 5000K Daylight White, 120-277V Input, IP65

- Draws 20W of power for energy-efficient illumination
- Produces 5000K daylight-white light output
- Accepts 120-277VAC input for flexible power compatibility
- IP65 rated for indoor and outdoor use
- Rated for 50,000 hours of LED lifetime
- Backed by a 1-year warranty

OVERVIEW

The F-20W-UL is a 20W LED flood light designed for general-purpose illumination in indoor and outdoor commercial and industrial environments. Its compact form factor and broad voltage compatibility make it suitable for a range of installation contexts.

The fixture operates at 20W and produces a 5000K daylight-white output, supporting visibility in task and area lighting applications. It accepts input voltage from 120-277VAC, providing reliable operation across variable power supply conditions, and carries an LED lifetime rating of 50,000 hours.

SPECIFICATIONS

OPTICAL

Color Temperature	5,000 K
LED Lifetime	50,000 h

ELECTRICAL

Operating Voltage	120-277 V
Wattage	20 W

MECHANICAL

Product Dimensions	9 × 10 × 5 in
Weight	7.5 lb

ENVIRONMENTAL

IP Rating	IP65
-----------	------

ORDERING

Warranty	1 y
----------	-----

APPLICATIONS

- Building perimeter lighting
- Parking lot and driveway illumination
- Warehouse and loading dock areas
- Signage and facade accent lighting
- General outdoor area lighting

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
cct_k	5,000 K	pdf	high
led_lifetime_h	50,000 h	db	high
operating_voltage	120–277 V	db	high
wattage	20 W	db	high
product_dimensions	9 × 10 × 5 in	db	high
weight	7.5 lb	db	high
ip_rating	IP65	pdf	high
warranty_years	1 y	db	high

Specifications subject to change without notice.

REVIEW COPY