

1/2" Knuckle Mount Bracket for 75W Watt-Selectable LED Floodlight

OVERVIEW

The F-S-S75W-KM is a 1/2" knuckle mount bracket designed for use with the F-S75W-3CCT-UL Watt-Selectable LED Floodlight. It provides a standard half-inch pipe entry mounting point suitable for wall, pole, or surface installations where adjustable aiming of the floodlight is required.

The bracket is compatible with the FL05-55W and FL05-75W fixture sizes per the manufacturer's mounting configuration data. It allows the floodlight to be repositioned and locked at the desired angle, supporting installations in general area lighting, doorway, pathway, and loading dock applications.

The parent floodlight carries UL/cUL listing and DLC 5.1 Premium qualification, and is backed by a 5-year warranty. Consult the floodlight datasheet for full fixture specifications before specifying this accessory.

SPECIFICATIONS

| | | | |
|----------------------|-------------|-----------------------|---------------|
| Power | 75 W | Input voltage | 120-277 VAC |
| Luminous flux | 9750 lm | Rated life | 50000 h |
| CCT | 2700-6500 K | Warranty | 5 years |
| CRI | 70 | Operating temp | -30 to +45 °C |
| IP rating | IP65 | | |

CERTIFICATIONS & COMPLIANCE



UL Listed

DesignLight
s
Consortium

IP65