

## COB SPI LED Strip Light, 360 Chips/m, 12W/m, 4000K, 24V DC, UL Listed

### OVERVIEW

The M-C-SPI-360-4K-24V-UL is a 5-meter roll of SPI-addressable COB LED strip light designed for dynamic lighting effects, including running water and chasing sequences. Driven by WS2811 IC, it is suited for architectural accent lighting, cove installations, and commercial display applications requiring pixel-level control at 24V DC.


The strip delivers 360 COB chips per meter at 12W/m, producing 780 lm/m at an efficacy of 65 lm/W with a 4000K neutral white CCT and a CRI of 90. The 180° beam angle provides broad, even illumination across the 10mm double-layer 2OZ PCB. The IP20 rating is appropriate for dry indoor installations. Operating temperature range is -25°C to +45°C. Cutting pitch is 83mm per segment.

This product is RoHS compliant and carries a 3-year warranty.

### SPECIFICATIONS

<b>Power</b>	12 W/m	<b>IP rating</b>	IP20 / IP66 / IP67 / IP68
<b>Luminous flux</b>	780 lm/m	<b>Input voltage</b>	24 V DC
<b>CCT</b>	2700, 3000, 4000, 6000 K	<b>Weight</b>	0.13 kg/roll
<b>CRI</b>	90 Ra	<b>Operating temp</b>	-25 to +45 °C
<b>Beam angle</b>	180 °		

### INSTALLATION



### CERTIFICATIONS & COMPLIANCE



RoHS