

## SMD2835 High-Voltage LED Strip Light, 120 LEDs/m, 10W/m, 5000K

### OVERVIEW

The M-HR-2835-120-50K is a high-voltage SMD2835 LED strip light designed for continuous-run commercial and residential accent, cove, and perimeter lighting applications. Operating at AC 120V, it requires no external driver and is available in multiple CCT options including 2700K, 3000K, 4000K, and 6000K.


The strip delivers 10W per meter and 900 lumens per meter with a 120° beam angle and a CRI greater than 80. LED density is 120 chips per meter. The IP66-rated construction resists dust ingress and high-pressure water jets, supporting both indoor and outdoor installations. Operating temperature range is -25°C to +45°C. The strip is cuttable at 50 cm or 100 cm intervals and is supplied in 50-meter rolls.

This product carries ETL, RoHS, CE, and UKCA certifications, confirming compliance with applicable North American and European safety and environmental standards. Installers should refer to the product manual prior to installation; AC terminals must not be contacted during or after installation. Consult your distributor for applicable warranty terms.

### SPECIFICATIONS

<b>Power</b>	10 W/m	<b>IP rating</b>	IP66
<b>Luminous flux</b>	900 lm/m	<b>Input voltage</b>	120 V AC
<b>CCT</b>	5000 K	<b>Dimensions</b>	12 mm W x 5 mm H
<b>CRI</b>	80	<b>Weight</b>	3.5 kg/roll
<b>Beam angle</b>	120 °	<b>Operating temp</b>	-25 to +45 °C

### INSTALLATION



## CERTIFICATIONS & COMPLIANCE

---



RoHS



IP66