



Indoor LED Wall Sconce, 5 W, 3000 K, 90-260 VAC, Gold and Black Aluminum and Glass

- 5 W draw at 3000 K warm white output
- Wide-range 90-260 VAC input for mixed supply conditions
- Rated efficacy of 100 lm/W
- Aluminum and glass body in gold and black finish
- Compact 3.5 in x 5.3 in (9 × 13.5 cm) wall profile
- 50,000-hour rated life with 1-year warranty

OVERVIEW

The KREVEXA indoor wall light is a compact aluminum and glass sconce finished in gold and black, measuring 3.5 in x 5.3 in (9 x 13.5 cm). It suits corridors, bedside walls, stairwells and other interior surface-mounted accent locations in hospitality and residential settings.

The luminaire draws 5 W at 3000 K warm white with a rated efficacy of 100 lm/W and a rated life of 50,000 hours. A wide 90-260 VAC input range covers standard North American and international supply conditions, and the fixture uses an E27 socket base.

Supplied with a 1-year warranty.

SPECIFICATIONS

OPTICAL

Luminous Flux	110 lm
Efficacy	100 lm/W
Color Temperature	3,000 K
LED Lifetime	50,000 h

MECHANICAL

Product Dimensions	9 × 13.5cm
Finish	Gold & Black
Material	Aluminum & Glass
Mounting	Wall mounted
Base Type	E27 Socket

ELECTRICAL

Operating Voltage	90-260 V
Wattage	5 W

ORDERING

Warranty	1 y
----------	-----

DIMENSIONS & DIAGRAMS

CCT	3000K
-----	-------

Lumens	100 lm/w
Power:	5W
Voltage:	90-260 VAC
Rated Life:	50,000 hours

FEATURES:

Combines sleek metal and glass for a sophisticated modern design statement.
Offers a warm and inviting glow perfect for cozy, intimate spaces.
Compact and versatile design complements a variety of contemporary interior styles.
Enhances your décor with its minimalist yet luxurious aesthetic appeal.
Crafted from premium materials ensuring durability and long-lasting performance.

1574 NW 108th Ave. Miami, FL 33172

www.poliledsigns.com

Tel: (305) 384-7550

DIMENSIONS

APPLICATIONS

Hotel corridors and guest room walls

Residential bedside and hallway accents

Stairwell and landing wall lighting

Restaurant and lounge interior walls

Office reception accent walls

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	110 lm	pdf	high
efficacy_lm_per_w	100 lm/W	db	high
cct_k	3,000 K	both	high
led_lifetime_h	50,000 h	pdf	high
operating_voltage	90–260 V	pdf	high
wattage	5 W	pdf	high
product_dimensions	9 × 13.5cm	pdf	high
finish	Gold & Black	db	high
material	Aluminum & Glass	db	high
mount_type	Wall mounted	pdf	medium
base_type	E27 Socket	db	high
warranty_years	1 y	db	high

Specifications subject to change without notice.