



LED Wall Lamp, 5 W, 3000 K, 100 lm,
IP20, Travertine and Metal Body, 120-
240 V AC

- 5 W integrated LED module rated at 100 lm/W efficacy
- 3000 K warm white output for residential interiors
- 50,000-hour rated LED life, temperature and fade resistant
- Travertine face with metal, wood and stone body in beige finish
- IP20, non-waterproof rating for dry indoor locations
- Compact 2.6 × 6.3 in (6.5 × 16 cm) wall-mounted profile

OVERVIEW

The Mireille Wall Lamp is a surface-mounted residential luminaire built from metal, wood and stone with a natural travertine face in a beige finish. Its streamlined geometric form suits dining rooms, living rooms, corridors and bedside wall positions in modern or transitional interiors.

The integrated LED module draws 5 W and delivers 100 lm at 3000 K in a warm white tone, with an efficacy of 100 lm/W and a rated life of 50,000 hours. Operation is on 120-240 V AC. The fixture measures 2.6 × 6.3 in (6.5 × 16 cm) and mounts flat against the wall on a smooth backing surface.

Rated IP20 and classified non-waterproof, the lamp is intended for dry interior locations only.

SPECIFICATIONS

OPTICAL

Luminous Flux	100 lm
Efficacy	100 lm/W
Color Temperature	3,000 K
LED Lifetime	50,000 h
Light Color	White

MECHANICAL

Product Dimensions	2.6 × 6.3in
Finish	Beige
Material	Metal, Wood & Stone
Mounting	Wall mount

ELECTRICAL

Operating Voltage	85-265 V
Wattage	5 W

ENVIRONMENTAL

IP Rating	IP20
Environmental Rating	Non-Waterproof

DIMENSIONS & DIAGRAMS

CCT	3000K	Lumens	100lm/w
IP rate	IP20	Power:	5 W
Environment Rating:	Non-Waterproof	Voltage:	120V - 240V AC
		Rated Life:	50,000 hours

FEATURES:

It is fashionable, warm, and vivacious

DIMENSIONS

APPLICATIONS

- Bedside wall lighting
- Dining and living room accent walls
- Corridors and hallways
- Hotel guest room headwalls
- Residential stairwell walls

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
lumens	100 lm	pdf	high
efficacy_lm_per_w	100 lm/W	db	high
cct_k	3,000 K	both	high
led_lifetime_h	50,000 h	pdf	high
color	White	db	high
operating_voltage	85–265 V	pdf	high
wattage	5 W	pdf	high
product_dimensions	2.6 × 6.3in	pdf	high
finish	Beige	db	high
material	Metal, Wood & Stone	db	high
mount_type	Wall mount	pdf	medium
ip_rating	IP20	both	high
environmental_rating	Non-Waterproof	db	high

Specifications subject to change without notice.