



Magnetic Track L Connector, Wall-to-Ceiling 90 Degrees, Black Aluminium Alloy, 85x39x29 mm

- Fixed 90-degree wall-to-ceiling transition for magnetic track runs
- Die-cast aluminium alloy body with black finish
- Compact 85 × 39 × 29 mm housing matched to Prolink track profiles
- IP20 rating for dry, non-waterproof interior installations
- Operating range of -20 to 60 degrees C
- Backed by a 5-year warranty and 50,000-hour system life rating

OVERVIEW

The Prolink Track System L Connector joins a wall-mounted magnetic track run to a ceiling-mounted run at a fixed 90-degree angle. It is used in retail interiors, galleries, showrooms and hospitality spaces where a continuous track line has to turn from a vertical to a horizontal plane without breaking the circuit.

The body measures 85 × 39 × 29 mm and is built from die-cast aluminium alloy in a black finish to match Prolink track profiles. It carries an IP20, non-waterproof rating for dry interior use and operates in ambient temperatures from -20 to 60 degrees C. The connected magnetic track platform is rated for 50,000 hours of service life.

Covered by a 5-year warranty.

SPECIFICATIONS

OPTICAL

Color Temperature	2,700 K
CRI	90
Beam Angle	24°
LED Lifetime	50,000 h

MECHANICAL

Product Dimensions	85×39×29 mm
Finish	Black
Material	Aluminium alloy
Mounting	Magnetic track, wall to ceiling

ORDERING

Warranty	5 y
----------	-----

ELECTRICAL

Operating Voltage	10 V
Wattage	15 W

ENVIRONMENTAL

IP Rating	IP20
Environmental Rating	Non-Waterproof
Ambient Operating Temperature	-20-60 °C -4-140 °F

APPLICATIONS

- Retail store interiors
- Art galleries and exhibition spaces
- Showrooms and display areas
- Hotel lobbies and hospitality interiors
- Office and reception ceilings

PROVENANCE — REVIEW COPY ONLY

slug	value	source	confidence
cct_k	2,700 K	pdf	high
cri	90	pdf	high
beam_angle_deg	24°	pdf	high
led_lifetime_h	50,000 h	pdf	high
operating_voltage	10 V	pdf	high
wattage	15 W	pdf	high
product_dimensions	85×39×29 mm	db	high
finish	Black	db	high
material	Aluminium alloy	db	high
mount_type	Magnetic track, wall to ceiling	pdf	medium
ip_rating	IP20	both	high
environmental_rating	Non - Waterproof	db	high
ambient_temp_c	-20–60 °C	db	high
warranty_years	5 y	db	high

Specifications subject to change without notice.