



Magnetic Track 90-Degree Triple Connector, 15 W, 2700 K, 24-Degree Beam, Black Finish

- 15 W integrated LED engine with 24-degree beam distribution
- 2700 K color temperature at CRI 90 for retail display work
- Die-cast aluminium alloy housing in black finish
- IP20 rating for dry, non-waterproof interior locations
- 50,000-hour rated LED lifetime
- Operates across a -20 to 60 degrees C ambient range

OVERVIEW

The Prolink triple connector joins three runs of magnetic track at 90 degrees while carrying an integrated 15 W light engine. Its 136 × 81 × 37 mm die-cast aluminium alloy body suits retail, gallery and hospitality ceilings where track branches change direction without a break in illumination.

Output is rated at 2700 K with CRI 90 through a 24-degree beam, with 0-10 V dimming control and a rated LED life of 50,000 hours. The IP20, non-waterproof assembly operates from -20 to 60 degrees C and mounts to wall or pole surfaces.

Covered by a 5-year warranty.

SPECIFICATIONS

OPTICAL

Color Temperature	2,700 K
CRI	90
Beam Angle	24°
LED Lifetime	50,000 h

MECHANICAL

Product Dimensions	136×81×37 mm
Finish	Black
Material	Aluminium Alloy Die Cast
Mounting	Wall/Pole Mount

ORDERING

Warranty	5 y
----------	-----

ELECTRICAL

Operating Voltage	10 V
Wattage	15 W
Dimmer Type	0-10 V

ENVIRONMENTAL

IP Rating	IP20
Environmental Rating	Non-Waterproof
Ambient Operating Temperature	-20-60 °C -4-140 °F

APPLICATIONS

Retail display ceilings

Showroom and gallery track runs

Hotel lobbies and corridors

Office reception areas

Museum exhibit lighting

slug	value	source	confidence
cct_k	2,700 K	pdf	high
cri	90	pdf	high
beam_angle_deg	24°	pdf	high
led_lifetime_h	50,000 h	pdf	high
operating_voltage	10 V	pdf	high
wattage	15 W	pdf	high
dimmer_type	0 - 10 V	pdf	medium
product_dimensions	136×81×37 mm	db	high
finish	Black	db	high
material	Aluminium Alloy Die Cast	db	high
mount_type	Wall/Pole Mount	db	high
ip_rating	IP20	both	high
environmental_rating	Non - Waterproof	db	high
ambient_temp_c	-20–60 °C	db	high
warranty_years	5 y	db	high

Specifications subject to change without notice.

REVIEW COPY