



Magnetic Track Light, 15 W, 2700 K, 24-Degree Beam, 377 x 27 mm Die-Cast Black

- 15 W output at 2700 K with CRI above 90
- 24-degree reflector beam for accent and display lighting
- Die-cast aluminum alloy heat sink in black finish
- 377 × 27 mm track section for DIY linear magnetic runs
- 0-10 V dimming control input
- Rated for -20 °C to 60 °C ambient and 50,000 hours

OVERVIEW

The Prolink Track System is a 377 × 27 mm black magnetic track light section for commercial interiors. The die-cast aluminum alloy body mounts as a DIY linear run, allowing luminaire heads to be positioned and repositioned along the track in retail, hospitality and gallery ceilings.

Each 15 W head delivers a 24-degree reflector beam at 2700 K with CRI above 90 for accent and display work. Rated IP20 and non-waterproof for dry indoor use, the system operates from -20 °C to 60 °C and carries a rated LED lifetime of 50,000 hours. 0-10 V dimming control is supported.

Backed by a 5-year warranty.

SPECIFICATIONS

OPTICAL

Color Temperature	2,700 K
CRI	90
Beam Angle	24°
LED Lifetime	50,000 h

MECHANICAL

Product Dimensions	377×27 mm
Finish	Black
Material	Aluminium Alloy Die Cast
Mounting	Magnetic track, DIY linear

ORDERING

Warranty	5 y
----------	-----

ELECTRICAL

Operating Voltage	10 V
Wattage	15 W
Dimmer Type	0-10V

ENVIRONMENTAL

IP Rating	IP20
Environmental Rating	Non - Waterproof
Ambient Operating Temperature	-20-60 °C -4-140 °F

APPLICATIONS

Retail display and merchandising ceilings

Showroom and gallery accent lighting

Hospitality lobbies and lounges

Commercial office reception areas

Museum and exhibition spaces

slug	value	source	confidence
cct_k	2,700 K	pdf	high
cri	90	pdf	high
beam_angle_deg	24°	pdf	high
led_lifetime_h	50,000 h	pdf	high
operating_voltage	10 V	pdf	high
wattage	15 W	pdf	high
dimmer_type	0-10V	pdf	high
product_dimensions	377×27 mm	db	high
finish	Black	db	high
material	Aluminium Alloy Die Cast	db	high
mount_type	Magnetic track, DIY linear	pdf	high
ip_rating	IP20	both	high
environmental_rating	Non - Waterproof	db	high
ambient_temp_c	-20-60 °C	db	high
warranty_years	5 y	db	high

Specifications subject to change without notice.

REVIEW COPY