POLI·LED

SKU SO-2STD-2USB-WH
Apr 24, 2026

Recessed Power Strip, 2-Outlet 2-USB, 12A 125V 1500W, White, ETL Listed

OVERVIEW

The SO-2STD-2USB-WH is a white recessed power strip designed for in-desk or surface-mount installations in commercial and office environments. It provides two AC outlets and two USB charging ports in a compact form factor, suitable for workstations, conference tables, and similar built-in applications.

The unit is rated at 12A, 125V, 60Hz, with a maximum load of 1500W. The housing measures 162 x 55 x 40mm and ships with a 1.5m AC power cable. Case material is 94V-0 rated ABS+PC. Operating temperature range is 0°C to 40°C with non-condensing humidity from 5% to 90% RH.

The product carries ETL listing and is RoHS compliant. A one-year warranty is included.

SPECIFICATIONS

Input voltage	90–264 Vac	**Input Current Max**	1200 mA
Input Frequency	47–63 Hz	**Hipot Test**	3000 Vac
Output Voltage 5v	4.75–5.35 Vdc	**Insulation Resistance**	>10 M:•
Output Current 5v	3 A	**Operating temp**	0–40 °C
Output Voltage 9v	8.55–9.45 Vdc	**Storage Temp C**	-20–85 °C
Output Current 9v	2.22 A	**Operating Humidity**	5–90 %RH
Output Voltage 12v	11.40–12.60 Vdc	**Dimensions**	162 x 55 x 40.6 mm
Output Current 12v	1.67 A	**Case Material**	94V-0 ABS+PC
Ripple Noise	200 mV	**Input Cable**	NEMA 3-pin, 16 AWG (1.31 mm²), SJT, 300V, 1.55 m, black
Holdup Time	10 ms	**Warranty**	2 years
Inrush Current	30 A		

DIMENSION

SHEET 图纸
ABOUT NO. 2
AC INPUT TYPE 入电插头型号
DC OUTPUT TYPE DC输出型号
DC OUTPUT CABLE DC电线规格
FABRICATION NO. LABEL 标牌
CASE MATERIAL 外壳材料 94V-0 ABS+PC
PCB MATERIAL PCB材料 94V-0
T SAFETY 安规
COMPLY SAFETY STANDARD 遵守安规标准
STANDARD 标准
FILE NO. 文件号
[T]
[T]
[T]

CERTIFICATIONS & COMPLIANCE

RoHS

Specifications subject to change without notice.