

NEMA 5-15P Straight Blade Plug, 15A 125V, 2-Pole 3-Wire, UL Listed

OVERVIEW

The SO-PLUG-2P-3W-UL is a NEMA 5-15P straight blade grounding plug rated for 15A at 125V, 2-pole 3-wire configuration. It is designed for use in commercial and residential wiring applications where a reliable, field-wireable plug termination is required.

The plug is constructed with PA6 nylon covers and base, brass line contacts, and zinc-plated steel terminal screws in a multiple-drive configuration. It accepts 14 AWG wire and is rated for operating temperatures from -40°C to 60°C. Flammability rating is V-2 per UL94, and the dielectric withstand is 2000V per UL498. Terminal identification follows standard color coding: brass for hot, silver for neutral, and green for ground.

This plug is listed to UL498 and CSA C22.2 No. 42 under File E355464, and conforms to NEMA WD-6 and ANSI C-73 standards. It carries a 1-year limited warranty.

SPECIFICATIONS

Input voltage	125 V	Warranty	1 years
Operating temp	-40 to 60 °C		

MOUNTING

Wire Gauge:	14 AWG
Standards and Certifications	
NEMA:	WD-6
ANSI:	C-73
UL498& CSA C22.2 No. 42:	File E355464
Warranty:	1 Year Limited

Dimensional Drawing :

LUMIPRO